

Glancetron 1288 Compact Magnetic Card Reader



- Favourably priced, compact reader for magnetic cards
- Completely freely programmable for high data security
- Versions for different tracks of the magnetic card
- Suitable for credit, EC, customer and many other card systems
- Simple connection: keyboard wedge, serial or USB

Specifications

General	
Decoding Capability	ISO-7811 single track: track 1, track 2 and track 3; ISO-7811 dual track: tracks 1 and 2, tracks 2 and 3; ISO-7811 triple track: tracks 1, 2 and 3
Magnetic Head Life	300,000 passes
Card Reading Speed	Bi-directional, 7.5 - 125 cm/sec
System Compatibilities	The standard RS232C and keyboard interface operate with IBM AT, PS/2 and Compatibles. The USB interface operates with a USB port on IBM AT or compatibles.
Power	Model MCR K: from KB port, 5V / Model MCR R: from external power supply, 5V / Model MCR U: from USB port, 5V
Dimensions	115 mm X 46 mm X 34 mm (W x H x D)
Weight	100 g
Colour	White & dark grey
Operating Temperature	0° C - 45° C (32° F - 113° F)
Operating Humidity	0% - 80% RH non-condensing
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Storage Humidity	10% - 90% RH non-condensing
Certification	FCC, CE, RoHS, Class A



Your Dealer