

Glancetron 8802

Complete POS-System - Robust and Compact



- Compact all-in-one system in miniature format – ideal for POS and hospitality
- Affordable entry-level version (Easy) or high-end processor (Ultimate)
- Top processing speed and performance thanks to Intel i5 mobile processor (2.4 GHz) (Ultimate)
- Brilliant contrast 30.7 cm (12.1") touch display

Specifications

Hardware	8802 Easy	8802 Ultimate
CPU	Intel Celeron M with 1 GHz	Intel i5 mobile processor with 2.4 GHz
Memory	1 GB DDR2 400 SDRAM (max. 2 GB)	1 GB DDR3 800/1066 SDRAM (max. 8 GB)
I/O ports	1x VGA, 1x gigabit Ethernet, 3x audio (Mic-in, line-out, line-in), 4x USB, 2x RS232, 2x PS/2, 1x LPT	1x VGA, 1x DVI, 2x gigabit Ethernet, 3x audio (Mic-in, line-out, line-in), 4x USB, 2x RS232, 2x PS/2
HDD	160 GB SATA II	160 GB SATA II
General		
Display	30.7 cm (12.1") TFT colour display with touch screen	
Resolution	1024 x 768 pixels	
Options	Integrated magnetic stripe reader (track 1, 2, 3), RFID reader (13.56 MHz Mifare), customer display (2x20 characters) integrated on rear side, dvd device and smart card reader	
Power in/out	110V~240V/5V, 12V internal power supply	
Dimensions	275x295x135 mm (WxDxH)	
Weight	6 kg	
Colour	Black/White	
Environment		
Operating temperature	0 ~ 50 °C (32 ~ 122 °F)	
Operating humidity	0 ~ 90 % relative humidity, non-condensing	



Your Dealer